

- 1/3" SONY CCD
- High Resolution 560TVL
- Built-in 9~22mm IR Auto Iris Lens
- 0.001 Lux Slowshutter (Sense up to 32X) 0 LUX with IR LEDs ON
- SNDR (Super Digital Noise Reduction)
- 12 High Intensity LEDs
- IP66 Weatherproof Housing
- Dual Power: AC24V / DC12V 700mA
- Cable Concealment Bracket



Specification

Detail

Type:	High Resolution Color Camera
Pickup device:	1/3" SONY CCD & DSP Image Sensor
Picture Elements:	NTSC: 811(H)x508(V) PAL: 795(H)x596(V)
Resolution:	560TVL
Horizontal Frequency:	1/3" SONY High Resolution CCD
Vertical Frequency:	NTSC: 60Hz PAL:50Hz
Scanning System:	2:1 Interface
IR LEDs	12 High Intensity IR LEDs
Sync System:	Internal
S/N Ratio:	>48dB
Mini Illumination (F1.030IRE):	0.001 LUX (Slowshutter 32X)
Electronic Shutter:	up to 1/100.000 sec
White Balance:	ATW: Auto Trace white balance
IR Range:	20~200 feet
Lens:	9~22mm Auto Iris Lens
Gamma:	0.45
Video Output:	1Vp-p , 75Ohms
Gain	Auto
Power Supply:	DC12V or AC24V (±10%)
Power Consumption:	700mA
Dimension L x W x H (mm)	18 x 13 x 10cm
Weight:	1300g / 2.8lbs
Storage Temperature:	-30°C ~ +60°C
Operating Temperature:	-10°C ~ +50°C