

Introduction :

- Standalone 4Ch DVR Kit with 4 Cameras.
- H.264 Compression, Pentaplex System
- 1 HDD SATA , max 2T capacity
- 1xBNC and 1xVGA Output
- 4 x 60feet Cables
- 1 DC12V 2.0A Power Adapter
- 1/4" Color CCD Camera, 26 IR LEDs, 3.6mm Lens w/ IR CUT



Product Features :

Specs	Model	
	PKG-DVR04	
System	Main Processor	High Performance Embedded Processor
	System Resource	Pentaplex: Live Recording, Playback, Backup, Remote Access, PTZ Control, Mobile Monitoring
	Control Mode	Front Panel, USB Mouse, IR Remote Control, Keyboard, Network
Video	Input	4 x BNC(1.0Vp-p, 75Ω)
	Standard	D1:NTSC 120FPS / PAL 100FPS CIF:NTSC 120FPS / PAL 100FPS
	Output	1 x BNC (1.0Vp-p, 75Ω), 1 x VGA
Audio	Audio Input	RCAx4
	Audio Output	RCAx1
	Display Split	4-Jan
Display	Resolution	VGA:1280 x 1024 / 1021 x 768 / 800 x 600
	Tour Display	Support
	OSD	Camera Title, Time, Video Loss, Motion Detection, Recording
Recording	Video/Audio- Compression	H.264 / ADPCM
	Image Resolution	D1:(720 x 576 / 720 x 480),HD1:(720 x 288 / 720 x 240) CIF:(352 x 288 / 352 x 240)
	Encoding Main	D1:120FPS
	Stream Extra	CIF:60FPS
	Recording Mode	Manual, Schedule (Regular Continuous), MD(Motion Detection,Video loss,Blank Screen),Alarm, Stop
	Recording Priority	Manual > Alarm > Motion Detection
Video Detection & Alarm	Trigger Events	Recording / PTZ Movement / Alarm / E-mail
	Motion Detection	Zones:396 (22 x 18), Sensitivity: 1-5
	Video Loss	Support
Playback & Backup	Playback Channel	4CH
	Playback Speed	D1:60FPS / CIF:120FPS
	Search Mode	Time / Date / Alarm / Motion Detection
	Playback Function	Play,Pause,Stop,Fast Forward,Slow Forward,Full Screen... (Recording Files can be viewed by dragging the progress bar back and forth.
	Backup Mode	U-Disk / Hard Disk / USB / CD / DVD-RW / Download
Network	Physical Interface	RJ-45port(10/100M)
	Network Function	TCP/IP, DHCP, DDNS, NTP, SMTP,DNS,IP Filter,PPPOE,E-mail,Alarm Server,UPNP,DNS Binding
	Remote Operation	Monitor, PTZ Control, Playback, System Setting, Files Download, Log Information
	Mobile Monitoring	Supports Windows Mobile, Symbian,Android,Iphone,Blackberry.....
Storage	HDD	4SATA
	Space Occupation	Audio:14.4MB/H , Video:56-900MB/H
	HDD Management	Hard Disk Hibernation Technology, HDD Faulty Alarm, File Restoration
Aux. Interface	USB	2-USB 2.0 Interface (for Mouse , U-Disk or USB HDD)
	PTZ	PTZ Control
Environment	Power Supply	DC12V / 2.0A
	Working	-10°C~+55°C / 10%~90% RH / 86~106Kpa
	Dimension	250 x 235 x 45mm (Product Size)
	Weight	2.0Kg (W/O HDD)

Camera Specs	
Pickup Device	1/4" SONY Color CCD with IR Cut
System	NTSC
Scanning System	2:1 Interface
IR LED Qty	26
IR Distance	60 Feet
Infrared Wavelength	850nm
Pixels	NTSC:768(H) x 494(V) - PAL:752(H) x 582(V)
Horizontal Resolution	480TVL
Vertical Frequency	NTSC:60Hz - PAL:50Hz
Gamma	0.45
Min.Illumination	0 LUX(IR ON)
Lens	3.6mm~16mm
Electronic Shutter	NTSC:1/60~1/100.000s / PAL:1/50~1/10.000s
S/N Ratio	48dB
Video Output	1Vp-p, 75Ω
Power Supply	DC12V
Operation Temp.	-10°C~+45°C
Housing	Plastic

* Pictures and specifications are subject to change without prior notice

